

COMPANY _____
 CONTACT NAME _____
 ADDRESS _____


 PHONE _____ FAX _____
 EMAIL _____

Replacement Cables

Cables are available in 30 series (3/16"), 40 series (1/4"), and 60 series (5/16"). The series is determined by the size of the threaded ends. Measurement of cable from very end to very end determines length. Cable travel (usually 3" or 4") is the distance of rod end movement when it is stroked as far as possible to prevent threads from contacting rod seals on both ends.



Bulkhead cables have double nuts and washers for mounting.



Clamp cables have grooves for mounting.

Cable Configurations	Mixer Manufacturer Control
30 Series, Bulkhead x Clamp, 3" Stroke	Rex throttle control
40 Series, Bulkhead, 3" Stroke	CMC front control Jaeger front control MTM front control, old style Rex front control Smith front control
40 Series, Bulkhead, 4" Stroke	Challenge front control MTM front control, new style MTM rear control, new style
40 Series, Bulkhead X Solid Wire, 3" Stroke	CMC throttle control Jaeger throttle control MTM throttle control, old style Smith throttle control
40 Series, Bulkhead X Solid Wire, 4" Stroke	MTM throttle control, new style
40 Series, Bulkhead X Strand Wire, 5" Stroke	Challenge throttle cable
60 Series, Bulkhead, 3" Stroke	CMC rear control Jaeger rear control Rex rear control Smith rear control
60 Series, Bulkhead, 4" Stroke	Challenge rear control